Straight Arm

Swivel Arm X-Ray System

The Universal Straight Arm system is an easy to operate, economical solution that accommodates all conventional imaging techniques in seated, standing or recumbent positions. The constant alignment of the x-ray tube and bucky guarantees fast and precise positioning.





Straight Arm

SWIVEL ARM X-RAY SYSTEM



Technical Specifications

Vertical
Movement: 16.5in (42cm) to 64in (163cm)

10.5111 (42cm) to 64111 (165cm)

Power supply: 115, 208, 230, 240 VAC;

single phase, 350 VA

Dimensions: height; 98.4in (250cm); width; 90.5in

(230cm) x depth; 47.8in (121.5cm)

Brakes: electromagnetic locks (24 V DC)

Range of

rotation: +135° to -35°

Bucky: with 17in x 17in (43cm x 43cm) grid

cabinet (max. cassette size: 43 x 43cm)

- friction locked angulation motion range

of $\pm 30^{\circ}$

- flat locking rails for accessories

Grid: 103 lines; ratio 10:1

Generator: 40kW, 500mA, CM Series high

frequency generator

X-Ray tube: 125kVp, 200kHU, 0.6-1.5mm with

3in anode, 14° target

Collimator: Manual collimator with laser light

centering and collimator swivel mount allowing 360° with 90° detents

Cables: One pair of 30ft high voltage generator

cables, terminated at both ends


Product Options

· AEC ion chamber

 Mobile table with laminate or carbon fiber table top: length: 78.7in (200cm), width: 25.6in

(650mm), height: 27.5in (70cm)

 A variety of generator, grid and tube options are also available



DEL MEDICAL

Toll Free: (800) 800-6006 Fax: (847) 288-7011 Email: info@delmedical.com www.delmedical.com Universal
Universal branded products are manufactured and

distributed by UMG/Del Medical.

Del Medical is an ISO 13485 & ISO 9001 Certified facility.

Specifications are subject to change without notice.

UMG

Toll Free: (800) 261-9808 Fax: (914) 835-6111 Email: info@umgxray.com

www.umgxray.com